Chair



More information on the sourcing of materials and regional compliance for this product can be requested from naughtone or found at www.naughtone.com \odot











Design

Called the Bounce chair due to the independent movement of the seat and back, this flex provides a comfort not usually associated with steel and plywood.

A distinct lack of visible fixings allows the Bounce chair to bring a level of sophistication to an interior, making it particularly popular in educational and casual meeting spaces, cafes and work place break out zones.

Technical

The Bounce chair is constructed from one piece of steel tube frame, finished with a hard wearing polyester powder coat finish. The seat and back rest are veneer faced moulded plywood, making the chair easy to lift, re-position and stack neatly.

*All dimensions quoted are rounded to the nearest 5mm or nearest 1/2 inch.

Base Finishes



White powdercoated frame as standard



Black powdercoate frame as standard



in naughtone RAL colou selection

Seat and Back Finishes



Standard Oak



Walnut



















Bounce chair technical specifications

Testing

Our chairs are designed to meet or exceed all EN performance requirements per EN16139:2013, which includes the following tests:

- Seat and back static load test
- Seat front edge static load test
- Vertical static load on back
- Foot rest and leg rest static load test
- Arm sideways static load test
- Arm downwards static load test
- Vertical upwards static load on arm rests

- Seat and back durability test
- Seat front edge durability test
- Leg forward static load test
- Leg sideways static load test
- Seat impact test
- Back impact test
- Arm impact test

Servicing

If a component is damaged and needs replacing then please email our team with an image of the damaged part and reference your order number, we will be happy to facilitate any replacements.

K

151

Warranty

naughtone offers a **5-year** warranty across all products. Details on the terms and conditions of naughtones warranty can be found <u>here</u>

Bounce chair technical specifications



Product code and description	A Overall Width	B Overall Depth	C Overall Height	D Seat Height	E Seat Width	F Height from seat to top	G Weight
1 BOUCH	555mm	550mm	750mm	450mm	420mm	300mm	6.5kg
Bounce chair	22in	21.5in	29.5in	17.5in	16.5in	12in	14.3lbs

Dimensions Guide







Structural testing certifications

BOUCH **Bounce Chair** BS EN 16139:2013, Level 1 Static load 160kg





Bounce chair environmental product summary



Environment attributes

- naughtone is FISP and ISO14001 certified
- naughtone is **FSC**[®] certified
- 6.5kg total weight
- 72.09% Recyclable (frame, fixings and feet)
- 27.01% Reusable (seat/back)
- 44.1% Recycled content (frame and fixings)
- Indoor Advantage[™] Gold ANSI/BIFMA Furniture Emissions Standard (M7.1/X7.1-2011 R2016) and ANSI/BIFMA e-3-2014e (Credits 7.6.1, 7.6.2, 7.6.3)

These attributes can help you to achieve criteria towards LEED, BREEAM, Ska and WELL building certifications













Bounce chair environmental product summary



CSR statement

naughtone has always considered the environment throughout our design and manufacturing process. We understand that as we continue to grow, so does our potential impact on our surroundings. As most of our raw materials are simple, we have great control over their sources, and are proud be able to offer FSC® certified upholstered products and use recycled metals in our table ranges. The addition of our North American manufacturing provision also helps to keep manufacturing miles to a minimum, as our market continues to grow in the USA. Finally, naughtone offers a 'bring back' programme, where the client is able to return the product to our factory, where we will be happy to breakdown and recycle the parts for you.

Where sustainable sources are quoted, and a chain of custody is required by a customer this must be indicated on the purchase order to naughtone A chain of custody requested after an order has been placed or delivered may be difficult to recover Figures stated in the Environmental product summary may vary based on model and options selected, we have based this document on a specific example when produced in the United Kingdom. Recycled content calculations are taken from supplier information and industry averages, material variables are likely to affect the figures which may result in higher or lower percentages

This document will be reviewed and updated periodically and is subject to change without notice

FSC[®] certified products leuponreques

Post Consumer Recycled Content



Product specific design statement

The Bounce chair frame is machine bent from mild steel tube which is then weld jointed together and hand polished to a smooth surface. The frame also has strengthening sleeves internally to assist the strength and bounce of the cantilever shape. The frame is then finished with a polyester powder coat.

The Bounce chair seat and back are both made from moulded beech plywood and faced with either oak or walnut veneer. The surface finish is a hard wearing spray matt lacquer. The plywood pieces and frame are assembled together by hand using minimal fixings and can be easily disassembled if necessary.



1 Design

Every aspect of the naughtone product ranges has been designed with the environment considered, from ethical material choice and production efficacy to storage efficiency and ease of disassembly.

Dense foam sets and resilient fabrics are selected for their longevity and effectiveness across sectors. Durable high quality finishes such as powder coated bases in a range of colours allow clients the freedom of finish options. Finish samples are available allowing clients to make informed decisions and retain to add to their finish libraries for future reference.

2 Raw Material

Local supply of raw materials is employed for the production of our products when possible, procured from suppliers that are quality inspected for extraction methods and meet the highest environmental standards.

3 Production

As many of our products are assembled by hand the energy expenditure wasted from machinery during the production process is kept to a minimum.

All fabrics are cut to ensure optimum efficiency with fabric usage and reduced waste consumption per unit.

All production sites have recycling facilities for any excess product that cannot be used elsewhere, which is then managed by a professional third party.

4 Distribution

Distribution of naughtone products generally occurs directly between the manufacturing site to the client. Production is localised when possible to the US or UK regions, reducing the carbon footprint and miles travelled for each product.

Many items are flat packed for delivery or shipped disassembled with efficient, minimised packaging; optimizing the transportation vessel space.



naughtone products do not require energy or water to function, thus no environmental exchange takes place and no waste is generated during the life of the product.

The only foreseeable need is the cleaning of the product for general maintenance. This includes regular vacuuming to remove dirt and dust particles on upholstery items, and using a dry or damp cloth to wipe non-upholstery items.

This is recommended for all products utilised under conditions of normal wear and is expected to have negligible environmental impacts.



Although our products are durable and demonstrate timeless design, naughtone products are manufactured in such a way that they can be easily disassembled at the end of life and most of the componentry can be either recycled or re-used as applicable.

As a company we are also happy to accept the return of products, to help re-home or recycle furniture or components at the end of the products useful life.

naughtone

Useful Beautiful Furniture British Designed Since 2005

UKShowroom

6 Bakers Yard Clerkenwell London EC1R3DD T: +44 (0)20 389 22 788

US Showroom

Suite 10–110 222 Merchandise Mart Plaza, Floor 10 Chicago IL 60654

naughtone HQ

Knaresborough Tech Park Manse Lane Knaresborough HG58LF

T:+44(0)1423816500

www.naughtone.com